



SHOP EQUIPMENT

**Single-Stage Air Compressor - 6HP,
60 Gallon Vertical**



Start/Stop pressure switch control Cast iron compressor pump Thermally protected motor Fully enclosed belt guard 60 gallon vertical tank with drain and discharge valve All Bel Aire air compressors are tested at full pressure by the factory before shipment Made in the USA Specifications: ACFM @ 100 PSI: 12.35; 14.55 @ 40 PSI Max PSI: 130 Motor: 208-230V/1Ph. - 15 AMP CFM Displacement: 16.80

**Part#
BEL6061V**

**Two-Stage Air Compressor - 5HP,
80 Gallon Vertical**



Model T39 2-stage compressor pump - solid cast iron cylinders, oversized ball bearings, splash lubrication No magnetic starter required Stop/Start pressure switch with pressure unloader and tank pressure gauge included 80 gallon vertical tank built to ASME code, includes bottom drain and side outlet valve. Fully enclosed belt guard 2 year "Bumper to Bumper" warranty Made in the USA Specifications: ACFM @ 100 PSI: 18.50 Max PSI: 175 Motor: 208-230V/1Ph. - 22 AMP CFM Displacement: 22.43

**Part#
BEL318V**



Two-Stage Air Compressor - 5HP 80 Gallon Vertical



Model T29 2-stage compressor pump - Solid cast iron cylinders, balanced iron crankshaft, ball bearing crank support, stainless steel valves Pre wired motor - No magnetic starter required Thermally protected motor Stop/Start pressure switch with pressure unloader and tank pressure gauge included 80 gallon vertical tank built to ASME code, includes bottom drain and side outlet valve. Fully enclosed belt guard 2 year "Bumper to Bumper" warranty Made in the USA Specifications: ACFM @ 100 PSI: 15.33 CFM CFM Displacement: 18.59 CFM Max PSI: 175 Motor: 208-230V/1Ph. - 22 AMP

Part#
BEL218V



Two-Stage Air Compressor - 7-1/2 HP 80 Gallon Vertical



Model T39 2-stage compressor pump - solid cast iron cylinders, oversized ball bearings, splash lubrication The industrial grade cast iron crank, industrial grade connecting rods and pistons are balanced for smooth operation and long life. Prewired magnetic starter Stop/Start pressure switch with pressure unloader and tank pressure gauge included 80 gallon vertical tank built to ASME code, includes bottom drain and side outlet valve. Fully enclosed belt guard 2 year "Bumper to Bumper" warranty Made in the USA Specifications: ACFM @ 100 PSI: 25.25 CFM Displacement: 32.52 CFM Max PSI: 175 Motor: 208-230V/1Ph. - 32/29 AMP

Part#
BEL318VL



SHOP EQUIPMENT

Two-Stage Air Compressor - 11HP



Part#
BEL3G3HH

11 HP Honda gasonline powered engine Rugged 2-stage cast iron compressor pump Electric start (retains recoil start also) 12 volt alternator Oil monitor Engine slowdown (pilot valve) 30 gallon horizontal tank with drain, pressure gauge Fully enclosed belt guard Covered by Bel Aire's "Bumper to Bumper" warranty for two full years Made in the USA Specifications: ACFM @ 100 PSI: 18.50 Max PSI: 175 CFM Displacement: 22.43

Two-Stage Air Compressor - 13HP



Part#
BEL3G3HHL Honda Engine
BEL3G3HKL Kohler Engine

BelAire engine driven air compressors provide solid performance and reliability. Features: 12Volt Electric & Recoil Start. * 12Volt Alternator. * Start key/panel. * Oil monitor. * Engine slowdown (pilot valve). * Fully enclosed belt guard. * Pull-type tank drain. * ASME safety valves. * Tank discharge valve. * 100% factory tested at full pressure before shipment. * Full two-year warranty covering the entire machine from BelAire. * BelAire Compressors are Made in the USA. Specifications: * Pump: T39 * Horsepower: 13 * Engine: Honda or Kohler* Tank (gal): 30H * CFM Displacement: 32.52 * ACFM @ 175 PSI: 22.28

